



CSIC
CONSEJO SUPERIOR DE INVESTIGACIONES CIENTÍFICAS



**INSTITUTO DE CIENCIAS
DE LA CONSTRUCCIÓN
EDUARDO TORROJA**

C/ Serrano Galvache, 4. 28033 Madrid (Spain)
Tel.: (+34) 91 302 0440 www.ietcc.csic.es
gestiondit@ietcc.csic.es dit.ietcc.csic.es



Member of



European Technical Assessment

ETA 23/0288
21/04/2025

English translation prepared by IETcc. Original version in Spanish language

General Part

Technical Assessment Body issuing the European Technical Assessment:

Instituto de Ciencias de la Construcción Eduardo Torroja (IETcc)

**Trade name of the construction
product**

Anchors BLPT, BLPC, BLPE

**Product family to which the
construction product belongs**

Torque controlled expansion anchor made of steel of sizes
M6, M8, M10, M12, M16 and M20 for use in concrete.

Manufacturer

Ningbo Bigood Metal Technology Co. Ltd.
No. 19, Eastern Section of Hongtang South Road
Ningbo, China.
website: www.nbbigood.com

Manufacturing plant

Ningbo Bigood Metal Technology plant 1

**This European Technical
Assessment contains**

13 pages including 3 annexes which form an integral part
of this assessment.

**This European Technical
Assessment is issued in accordance
with Regulation (EU) No 305/2011,
on the basis of**

European Assessment Document EAD 330232-01-0601
"Mechanical Fasteners for use in concrete", ed. December
2019

This ETA replaces

ETA 23/0288 revision 1 dated 30/01/2025



Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such



SPECIFIC PART

1. Technical description of the product

The Bigood BLPT heavy duty anchor product in the range of M6, M8, M10, M12, M16 and M20 is an anchor made of galvanised steel. BLPT anchor have a hexagonal head; BLPC anchor have countersunk head and the BLPE is the projecting bolt version. The anchor is installed into a predrilled cylindrical hole and anchored by torque-controlled expansion. The anchorage is characterised by friction between the expansion sleeve and the concrete.

Product and installation descriptions are given in annex A1.

2. Specification of the intended use in accordance with the applicable European Assessment Document.

2.1 Intended use

This ETA covers fasteners to be used in compacted, reinforced or unreinforced, normal weigh, cracked or uncracked concrete without fibers with strength classes in the range of C20/25 to C50/60 all in accordance with EN 206, for static or quasi-static or under seismic actions (categories C1 and C2) and with requirements related to fire exposure, loaded in tension, shear or combined tension and shear.

The performances given in section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in annex B1.

2.2 Relevant general conditions for the use of the product

The assessment methods included or referred to in this EAD have been written based on the manufacturer's request to take into account a working life of the fastener for the intended use of 50 years when installed in the works (provided that the fastener is subject to appropriate installation). These provisions are based upon the current state of the art and the available knowledge and experience.

When assessing the product, the intended use as foreseen by the manufacturer shall be taken into account. The real working life may be, in normal use conditions, considerably longer without major degradation affecting the basic requirements for works.

The indications given as to the working life of the construction product cannot be interpreted as a guarantee neither given by the product manufacturer or its representative nor by EOTA when drafting the EAD nor by the Technical Assessment Body issuing an ETA based on this EAD, but are regarded only as a mean for expressing the expected economically reasonable working life of the product.

This ETA covers fasteners for installation in pre-drilled holes in compacted reinforced or unreinforced normal weight concrete without fibers considering annexes B and C.

3. Performance of the product and references to the methods used for its assessment

The identification tests and the assessment for the intended use of this product according to the Basic Work Requirements (BWR) were carried out in compliance with EAD 330232-01-0601. The characteristics of each system shall correspond to the respective values laid down in following tables of this ETA, checked by IETcc.

Methods of verification and of assessing and judging are listed afterwards.



3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Relevant clause in EAD	Performance	Annex
Resistance to steel failure	2.2.1	$N_{Rk,s}$ [kN]	C3, C4
Resistance to pull-out failure	2.2.2	$N_{Rk,p}$ [kN] ψ_c [-]	C3, C4
Resistance to concrete cone failure	2.2.3	$k_{cr,N}$, $k_{ucr,N}$ [-] h_{ef} , $c_{cr,N}$ [mm]	C3, C4
Robustness	2.2.4	γ_{inst} [-]	C3, C4
Minimum edge distance and spacing	2.2.5	c_{min} , s_{min} , h_{min} [mm]	C1
Edge distance to prevent splitting under load	2.2.6	$N^0_{Rk,sp}$ [kN], $c_{cr,sp}$ [mm]	C3, C4
Resistance to steel failure under shear load	2.2.7	$V^0_{Rk,s}$ [kN], $M^0_{Rk,s}$ [Nm], k_7 [-]	C5, C6
Resistance to pry-out failure	2.2.8	k_8 [-]	C5, C6
Displacement under static and quasi-static loading	2.2.10	δ_{N0} , $\delta_{N\infty}$, δ_{V0} , $\delta_{V\infty}$ [mm]	C3, C4, C5, C6
Resistance to seismic tension loads; displacements	2.2.11 2.2.12	$N_{Rk,s,C1}$, $N_{Rk,p,C1}$ [kN] $N_{Rk,s,C2}$, $N_{Rk,p,C2}$ [kN], $\delta_{N,C2}$ [mm]	C7, C8
Resistance to seismic shear loads; displacements	2.2.13 2.2.14	$V_{Rk,s,C1}$ [kN], $V_{Rk,s,C2}$ [kN], $\delta_{V,C2}$ [mm]	C7, C8
Factor for annular gap	2.2.15	α_{gap} [-]	C7, C8

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Relevant clause in EAD	Performance	Annex
Reaction to fire	2.2.16	Anchorage satisfy requirements for class A1 according to EN 13501-1	--
Fire resistance to steel failure, tension load	2.2.17	$N^0_{Rk,s,fi}$ [kN]	C9, C10
Fire resistance to pull out failure, tension load	2.2.18	$N^0_{Rk,p,fi}$ [kN]	C9, C10
Fire resistance to steel failure, shear load	2.2.19	$V^0_{Rk,s,fi}$ [kN] $M^0_{Rk,s,fi}$ [Nm]	C9, C10

3.3 Durability

Essential characteristic	Relevant clause in EAD	Performance	Annex
Durability: BLPT, BLPC, BLPE	2.2.20	Coated in zinc plated Coated in zinc nickel	A2



4. Assessment and Verification of Constancy of Performance (hereinafter AVCP) system applied, with reference to its legal base

The applicable European legal act for the system of Assessment and Verification of Constancy of Performance (see annex V to Regulation (EU) No 305/2011) is 96/582/EC.

The system to be applied is 1.

5. Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document.

Technical details necessary for the implementation of the AVCP system are laid down in the quality plan which is deposited at IETcc⁽¹⁾.

Prepared by: PhD Julián Rivera (Innovative Products Assessment Unit, IETcc-CSIC)

Issued in Madrid on 21st of April 2025

Mr. Ángel Castillo Talavera

Director

on behalf of Instituto de Ciencias de la Construcción Eduardo Torroja (IETcc – CSIC)

⁽¹⁾ The Quality Plan is a confidential part of the ETA and only handed over to the notified certification body involved in the assessment and verification of constancy of performance.




Product and installed condition

BLPT anchor



BLPC anchor




BLPE anchor




Identification on anchor:

- Sleeve: BLPT / BLPE: outer diameter / total length / maximum fixture thickness to be fixed.
BLPC: "C" / outer diameter / total length / maximum fixture thickness to be fixed
- Plastic ring: anchor name "BLP", company logo



- d_0 : Nominal diameter of drill bit
 d_i : Fixture clearance hole diameter
 h_{ef} : Effective anchorage depth
 h_1 : Depth of drilled hole
 h_{nom} : Overall anchor embedment depth in the concrete
 h_{min} : Minimum thickness of concrete member
 t_{fix} : Fixture thickness



BLPT, BLPC, BLPE anchors

Product description

Installed condition

Annex A1



Table A1: Materials

Item	Designation	Material for BLPT	Material for BLPC	Material for BLPE
1	Bolt	DIN 931 ISO 898-1 class 8.8. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0	DIN 7991 ISO 898-1 class 10.9. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0	---
2	Projecting bolt	---	---	Threaded stud class 8.8 ISO 898-1. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0
3	Nut	---	---	Standard nut class 8. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0
4	Washer	DIN 9021 or DIN 440. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0	Special conical washer. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0	DIN 9021 or DIN 440. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0
5	Sleeve	Carbon steel. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0		
6	Plastic ring	POM		
7	Expansion sleeve	Carbon steel. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0		
8	Cone	Hardened carbon steel. Galvanized $\geq 5 \mu\text{m}$ ISO 4042 Zn5/An/T0		

BLPT, BLPC, BLPE anchors	Annex A2
Product description	
Materials	



Specifications of intended use

Version	Intended use	M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
BLPT BLPC BLPE	Static or quasi static loads	✓	✓	✓	✓	✓	✓
	Seismic loads category C1		✓	✓	✓	✓	✓
	Seismic loads category C2		✓	✓	✓	✓	✓
	Resistance to fire exposure	✓	✓	✓	✓	✓	✓

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres according to EN 206-1:2013 + A2:2021.
- Strength classes C20/25 to C50/60 according to EN 206-1:2013 + A2:2021.
- Cracked or uncracked concrete

Use conditions (environmental conditions):

- Temperature range of the anchorage base material during the working life: -40 °C to +80 °C
- Anchorages subjected to dry internal conditions.

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete.
- Verifiable calculation rules and drawings are prepared taking into considering the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g., position of the anchor relative to reinforcement or to supports, etc.).
- Anchorages under static or quasi-static actions are designed for design method A in accordance with EN 1992-4:2018
- Anchorages under seismic actions are designed in accordance with EN 1992-4:2018. Anchorages shall be positioned outside of critical regions (e.g. plastic hinges) of the concrete structure. Fastening in stand-off installation or with grout layer are not allowed.
- Anchorages under fire exposure are designed in accordance with EN 1992-4:2018. It must be ensured that local spalling of the concrete cover does not occur.

Installation:

- Hole drilling by rotary plus hammer mode.
- Anchor installation carried out by appropriately qualified personal and under the supervision of the person responsible for technical matters of the site.
- In case of aborted hole: new drilling at a minimum distance away of twice the depth of aborted hole or smaller distance if the aborted hole is filled with non-shrinkage mortar with a strength at least or equal of the base material and $\geq 40 \text{ N/mm}^2$.

BLPT, BLPC, BLPE anchors

Intended use

Specifications

Annex B1




Table C1: Installation parameters BLPT, BLPC, BLPE

Installation parameters			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
d ₀	Nominal diameter of drill bit:	[mm]	10	12	16	18	24	28
d _f	Fixture clearance hole dia. ≤	[mm]	12	14	18	20	26	31
T _{inst}	Nominal installation torque:	[Nm]	15	30	50	80	160	240
h _{min}	Min. thickness of concrete member:	[mm]	100	120	140	170	200	250
h ₁	Depth of drilled hole ≥	[mm]	70	85	95	110	130	160
h _{nom}	Overall anchor embedment depth in the concrete:	[mm]	59	72	83	97	117	146
h _{ef}	Effective anchorage depth:	[mm]	50	60	70	85	100	125
t _{fix}	Thickness of fixture DIN 125 ≤ ¹⁾	[mm]	L - 60	L - 75	L - 85	L - 100	L - 120	L - 150
t _{fix}	Thickness of fixture DIN 440 ≤ ¹⁾	[mm]	L - 61	L - 76	L - 86	L - 101	L - 12	L - 151
S _{min}	Minimum spacing in uncracked concrete:	[mm]	60	70	80	100	125	150
	for c ≥	[mm]	125	150	195	220	255	405
C _{min}	Minimum edge distance in uncracked concrete:	[mm]	50	60	70	80	100	160
	for s ≥	[mm]	100	120	175	200	220	320
S _{min}	Minimum spacing in cracked concrete:	[mm]	50	70	70	80	120	120
	for c ≥	[mm]	95	110	145	165	190	310
C _{min}	Minimum edge distance in cracked concrete:	[mm]	50	60	70	80	100	160
	for s ≥	[mm]	60	70	80	100	125	150
d _c	Diameter of countersunk head in the fixture:	[mm]	16.4	20.6	26.8	30.8	38.8	44.8
h _c	Height of countersunk head in the fixture:	[mm]	3.2	4.3	5.4	6.4	7.4	8.4
SW	BLPT / BLPE socket size:	[--]	10	13	17	19	24	30
SW	BLPC hexagonal recess:	[--]	4	5	6	8	10	12

¹⁾ L = total anchor length

Installation procedure



BLPT, BLPC, BLPE anchors	Annex C1
Performances	
Installation parameters and installation procedure	



Table C2: Characteristic values to tension loads of design method A according to EN 1992-4 for BLPT, BLPC, BLPE anchors

Characteristic values of resistance to tension loads of design according to design method A			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
Resistance to steel failure								
N _{Rk,s}	Characteristic resistance:	[kN]	16.1	29.3	46.4	67.4	126.0	196.0
γ _{Ms}	Partial safety factor: ¹⁾	[-]	1.5					
Resistance to pull-out failure								
N _{Rk,p,ucr}	Characteristic resistance in C20/25 uncracked concrete:	[kN]	15.0	20.0	≥ N ⁰ _{Rk,c} ²⁾			
N _{Rk,p,cr}	Characteristic resistance in C20/25 cracked concrete:	[kN]	≥ N ⁰ _{Rk,c} ²⁾					
γ _{inst}	Robustness:	[-]	1.0	1.0	1.0	1.0	1.2	1.2
Ψ _c	Increasing factor for	[-]	1.22	1.22	1.22	1.22	1.08	1.08
	N ⁰ _{Rk,p} :	[-]	1.41	1.41	1.41	1.41	1.15	1.15
		[-]	1.58	1.58	1.58	1.58	1.20	1.20
Resistance to concrete cone and splitting failure								
h _{ef}	Effective embedment depth:	[mm]	50	60	70	85	100	125
k _{ucr,N}	Factor for uncracked concrete:	[-]	11.0					
k _{cr,N}	Factor for cracked concrete:	[-]	7.7					
γ _{inst}	Robustness:	[-]	1.0	1.0	1.0	1.0	1.2	1.2
s _{cr,N}	Spacing, edge distance for concrete cone failure:	[mm]	3 x h _{ef}					
c _{cr,N}		[mm]	1.5 x h _{ef}					
N ⁰ _{Rk,sp}	Characteristic splitting resistance:	[kN]	min (N _{Rk,p} ; N ⁰ _{Rk,c})					
s _{cr,sp}	Spacing, edge distance for splitting failure:	[mm]	205	245	285	345	410	510
c _{cr,sp}		[mm]	105	125	145	175	205	255

¹⁾ In absence of other national regulations

²⁾ Pull out failure is not decisive. $N_{Rk,c}^0$ calculated according to EN 1992-4

Table C3: Displacements under static and quasi-static tension loading for BLPT, BLPC, BLPE anchors

Displacements under tension loading			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
N	Service tension load in uncracked concrete C20/25 to C50/60:	[kN]	7.43	10.24	13.71	18.38	19.52	27.30
δ _{N0}	Short term displacement:	[mm]	1.18	2.02	1.79	1.15	2.46	2.12
δ _{N∞}	Long term displacement:	[mm]	2.68	2.68	2.68	2.68	2.68	2.68
N	Service tension load in cracked concrete C20/25 to C50/60:	[kN]	5.81	7.62	9.62	12.86	13.65	19.09
δ _{N0}	Short term displacement:	[mm]	1.75	2.69	2.57	3.53	1.76	2.41
δ _{N∞}	Long term displacement:	[mm]	3.75	4.69	4.57	5.53	3.76	4.41

BLPT, BLPC, BLPE anchors

Performances

Characteristic values for tension loads

Annex C2



Table C4: Characteristic values to shear loads of design method A according to EN 1992-4 for BLPT, BLPC, BLPE anchors

Characteristic values of resistance to shear loads of design according to design method A			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
Resistance to steel failure under shear loads								
V ⁰ _{Rk,s}	Characteristic resistance:	[kN]	20.2	33.0	62.2	75.1	111.2	141.7
k ₇	Ductility factor:	[-]	1.0					
M ⁰ _{Rk,s}	Characteristic bending moment:	[Nm]	12.2	30.0	59.8	104.8	266.4	519.3
γ _{Ms}	Partial safety factor: ¹⁾	[-]	1.25					
Resistance to pry-out failure								
k ₈	Pryout factor:	[-]	1.0	2.0	2.0	2.0	2.0	2.0
γ _{inst}	Robustness:	[-]	1.0					
Resistance to concrete edge failure								
l _f	Effective length of anchor under shear loads:	[mm]	50	60	70	85	100	125
d _{nom}	Outside anchor diameter:	[mm]	10	12	16	18	24	28
γ _{inst}	Robustness:	[-]	1.0					

¹⁾ In absence of other national regulations

Table C5: Displacements under static and quasi-static shear loading for BLPT, BLPC, BLPE anchors

Displacements under shear loading			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
V	Service shear load in uncracked and cracked concrete C20/25 to C50/60:	[kN]	9.62	15.71	29.62	35.76	44.13	56.23
δ_{V0}	Short term displacement:	[mm]	2.15	1.22	1.31	1.72	1.41	1.96
$\delta_{V\infty}$	Long term displacement:	[mm]	3.23	1.83	1.96	2.58	2.11	2.93

BLPT, BLPC, BLPE anchors

Performances

Characteristic values for shear loading

Annex C3



Table C6: Essential characteristics for seismic performance category C1 for BLPT, BLPC, BLPE anchors

Essential characteristics for seismic performance category C1			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
Resistance to steel failure under tension loads								
N _{Rk,s,C1}	Characteristic tension resistance:	[kN]	--	29.3	46.4	67.4	126.0	196.0
γ _{Ms}	Partial safety factor: ¹⁾	[-]	--	1.5				
Resistance to steel failure under shear loads								
V _{Rk,s,C1}	Characteristic shear resistance:	[kN]	--	23.1	43.6	45.0	77.9	99.4
α _{gap}	Factor for annular gap:	[-]	--	0.5				
γ _{Ms}	Partial safety factor: ¹⁾	[-]	--	1.25				
Resistance to pull-out failure								
N _{Rk,p,C1}	Characteristic pull out failure:	[kN]	--	13.0	16.2	24.7	31.3	46.3
γ _{inst}	Robustness:	[-]	--	1.0	1.0	1.0	1.2	1.2
Resistance to concrete cone failure								
h _{ef}	Effective embedment depth:	[mm]	--	60	70	85	100	125
Scr,N	Spacing:	[mm]	--	3 x h _{ef}				
Ccr,N	Edge distance:	[mm]	--	1.5 x h _{ef}				
γ _{inst}	Robustness:	[-]	--	1.0	1.0	1.0	1.2	1.2

¹⁾ In absence of other national regulations

Table C7: Essential characteristics for seismic performance category C2 for BLPT, BLPC, BLPE anchors

Essential characteristics for seismic performance category C2			Performances					
			M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
Resistance to steel failure under tension loads								
N _{Rk,s,C2}	Characteristic tension steel failure:	[kN]	--	29.3	46.4	67.4	126.0	196.0
γ _{Ms}	Partial safety factor: ¹⁾	[-]		1.5				
Resistance to steel failure under shear loads								
V _{Rk,s,C2}	Characteristic shear steel failure:	[kN]	--	16.5	33.8	30.1	55.6	54.7
α _{gap}	Factor for annular gap:	[-]	--	0.5				
γ _{Ms}	Partial safety factor: ¹⁾	[-]	--	1.25				
Resistance to pull-out failure								
N _{Rk,p,C2}	Characteristic pull out failure:	[kN]	--	6.1	12.1	21.4	34.4	40.8
γ _{inst}	Robustness:	[-]	--	1.0	1.0	1.0	1.2	1.2
Resistance to concrete cone failure								
h _{ef}	Effective embedment depth:	[mm]	--	60	70	85	100	125
S _{cr,N}	Spacing:	[mm]	--	3 x h _{ef}				
C _{cr,N}	Edge distance:	[mm]	--	1.5 x h _{ef}				
γ _{inst}	Robustness:	[-]	--	1.0	1.0	1.0	1.2	1.2
Displacements								
δ _{N,C2} (DLS)	Displacement Damage Limitation	[mm]	--	4,7	3,4	5,9	4,0	3,9
δ _{V,C2} (DLS)	State:	[mm]	--	4,9	5,2	5,8	6,0	6,1
δ _{N,C2} (ULS)	Displacement Ultimate Limit State:	[mm]	--	16.4	10.9	19.0	11.9	10.5
δ _{V,C2} (ULS)		[mm]	--	8.8	9.3	9.4	13.0	9.2

¹⁾ In absence of other national regulations

BLPT, BLPC, BLPE anchors	Annex C4
Performances	
Essential characteristics for C1 and C2 seismic performances	



Table C8: Characteristic values for resistance under fire exposure for BLPT, BLPC, BLPE anchors

Characteristic values under fire exposure				Performances					
				M6 Ø10	M8 Ø12	M10 Ø16	M12 Ø18	M16 Ø24	M20 Ø28
Fire resistance to steel failure									
N ⁰ _{Rk,s,fi}	Characteristic tension resistance:	R30	[kN]	0.2	0.4	0.9	1.7	3.1	4.9
		R60	[kN]	0.2	0.3	0.8	1.3	2.4	3.7
		R90	[kN]	0.1	0.3	0.6	1.1	2.0	3.2
		R120	[kN]	0.1	0.2	0.5	0.8	1.6	2.5
V ⁰ _{Rk,s,fi}	Characteristic shear resistance:	R30	[kN]	0.2	0.4	0.9	1.7	3.1	4.9
		R60	[kN]	0.2	0.3	0.8	1.3	2.4	3.7
		R90	[kN]	0.1	0.3	0.6	1.1	2.0	3.2
		R120	[kN]	0.1	0.2	0.5	0.8	1.6	2.5
M ⁰ _{Rk,s,fi}	Characteristic bending resistance:	R30	[Nm]	0.2	0.4	1.1	2.6	6.7	13.0
		R60	[Nm]	0.1	0.3	1.0	2.0	5.0	9.7
		R90	[Nm]	0.1	0.3	0.7	1.7	4.3	8.4
		R120	[Nm]	0.1	0.2	0.6	1.3	3.3	6.5
Fire resistance to pull-out failure									
N ⁰ _{Rk,p,fi}	Characteristic resistance:	R30 to R90	[kN]	3.0	4.8	7.1	11.5	17.2	30.1
		R120	[kN]	2,4	3.8	5.6	9.2	13.8	24.1
Fire resistance to concrete cone failure ¹⁾									
N ⁰ _{Rk,c,fi}	Characteristic resistance:	R30	[kN]	3.0	4.8	7.1	11.5	17.2	30.1
		R60							
		R90							
		R120	[kN]	2.4	3.8	5.6	9.2	13.8	24.1
S _{cr,N,fi}	Spacing:	R30 to R120	[mm]	4 x h _{ef}					
C _{cr,N,fi}	Edge distance:	R30 to R120	[mm]	2 x h _{ef}					
S _{min,fi}	Minimum spacing:	R30 to R120	[mm]	100	120	175	200	220	320
C _{min,fi}	Minimum edge distance:	R30 to R120	[mm]	C _{min} = 2 x h _{ef} ; if fire attack comes from more than one side, the edge distance of the anchor has to be ≥ 300 mm and ≥ 2 x h _{ef}					
Fire resistance to concrete pry-out failure									
k ₈	Pryout factor:	R30 to R120	[-]	1.0	2.0	2.0	2.0	2.0	2.0

- 1) As a rule, splitting failure can be neglected since cracked concrete and reinforcement is assumed.
2) In absence of other national regulations the partial safety factor for resistance under fire exposure $\gamma_{m,fi} = 1.0$ is recommended

BLPT, BLPC, BLPE anchors	Annex C5
Performances	
Characteristic values under fire exposure	

